

10K INGROUND EV1020

With its small footprint and substantial capabilities, this 10,000 lbs., 3-Stage inground lift is ready for any professional service facility. **Expect a longer life cycle from our chrome guide tubes and non-breathing ram-style cylinders.**

Optional productivity upgrades include our **XP9 Express Service Pad** for quick vehicle spotting and our **QuickCycle™** technology that reduces lift operation time.



MODEL # EV1020

All Ingrounds are fully contained to eliminate any risk of environmental impact.

CONCRETE SPECS
4" thick, reinforced, free from cracks & seams, rated at 3500+ psi & cured minimum of 28 days

REQUIREMENTS

-  **12' MINIMUM**
-  **12' RECOMMENDED**
-  **24' RECOMMENDED**
-  **208-230V, 1PH, 30A**
-  **90-120 PSI**

SPECIFICATIONS

MODEL NUMBER	EV1020 / EV1020-QC	EV1020XP9 / EV1020XP9-QC
Description	Standard / QuickCycle™	XP9 / XP9 & QuickCycle™
Lifting Capacity	10,000 lbs.	9,000 lbs.
Arm Configuration	3-Stage Front & Rear	Drive-on Express Pad
Stroke	68"	
Rise Height	74"	70"
Overall Width (A)	97"	79½"
Drive Thru Clearance (B)	7' 3"	NA
Arm Reach (C)	Min. 19⅝" Max. 42⅝"	NA
Platform Length x Width	NA	58"/66½"/75" x 24"
Distance Between Platforms	NA	31½"
Screw Pad Height	3⅞" - 6⅞"	NA
Plunger Diameter	8½"	
Standard Motor/Voltage*	2HP, 208v-230v, 60Hz, 1Ph / 3HP, 208v-230v, 60Hz, 1Ph	
Rise Time	38s / 24s	38s / 24s
Max. Load per Arm	2,500 lbs.	4,500 lbs.
ALI® Certified	<input checked="" type="checkbox"/>	

SERVICE BAY LAYOUT

