





12K HD ADJUSTABLE CL12A & CL12A-LC

Our 12,000 lbs. capacity 2-Post lift can accommodate a wide range of standard cars, trucks, vans, and SUVs within the same service bay. Standard features include 3-Stage front and rear arms.

Our CL12A-LC can be installed in shops with 12' ceilings.

SERVICE BAY SPECIFICATIONS

-  **HEIGHT:** 13' 3" minimum
-  **WIDTH:** 14' recommended
-  **DEPTH:** 24' recommended
-  **POWER:** 208-230v, 1pH, 20a

 **CONCRETE**
4" thick, reinforced, free from cracks/seams,
3500+ psi & cured 28+ days

PRODUCT SPECIFICATIONS

MODEL NUMBER	CL12A-LC	CL12A-LC-DPC-QC	CL12A	CL12A-DPC-QC
Description	Low-Ceiling	Low-Ceiling w/ DPC & QuickCycle™	Standard	Standard w/ DPC & QuickCycle™
Lifting Capacity	12,000 lbs.			
Lift Configuration	Symmetric			
Arm Configuration	3-Stage Front & Rear			
Rise Height	80¾"		84¾"	
Overall Height	11' 11"		13' 8" or 13' 2"	13' 8" or 13' 2"
Overall Width	Standard - 11' 10" +6" - 12' 4" +12" - 12' 10"			
Drive Thru Clearance	Standard - 8' 7½" +6" - 9' 1½" +12" - 9' 7½"			
Floor to Overhead Switch	11' 4½"		13' 2" or 12' 8"	13' 2" or 12' 8"
Arm Reach	Min. 27½" Max. 59"			
Screw Pad Height	Min. 5" Max. 12⅝" (includes 6" stack adapter)			
Rise Time	60s	38s	63s	40s
Min. Ceiling Height	12'		13' 9" or 13' 3"	13' 9" or 13' 3"

SERVICE BAY LAYOUT

