

10K INGROUND

EV1020

With its small footprint and substantial capabilities, this 10,000 lbs., 3-Stage inground lift is ready for any professional service facility.

REQUIREMENTS

-  **12' MINIMUM**
-  **12' RECOMMENDED**
-  **24' RECOMMENDED**
-  **208-230V, 1PH, 30A**
-  **90-120 PSI**

CONCRETE
4" thick, reinforced, free from cracks/seams,
3500+ psi & cured 28+ days



MODEL # EV1020

 All Ingrounds are fully contained to eliminate any risk of environmental impact.

SPECIFICATIONS

MODEL NUMBER	EV1020 / EV1020-QC
Description	Standard / QuickCycle™
Lifting Capacity	10,000 lbs.
Arm Configuration	3-Stage Front & Rear
Stroke	68"
Rise Height	74"
Overall Width (A)	97"
Drive Thru Clearance (B)	7' 3"
Arm Reach (C)	Min. 19 5/8" Max. 42 1/8"
Platform Length x Width	NA
Platform Width	NA
Distance Between Platforms	NA
Screw Pad Height	3 7/8" - 6 1/8"
Plunger Diameter	8 1/2"
Standard Motor/Voltage*	2HP, 208v-230v, 60Hz, 1Ph / 3HP, 208v-230v, 60Hz, 1Ph
Rise Time	38s / 24s
Max. Load per Arm	2,500 lbs.
ALI® Certified	☒

SERVICE BAY LAYOUT

