

10K INGROUND

EV1020-XP9

With its small footprint and substantial capabilities, this 10,000 lbs., 3-Stage inground lift is ready for any professional service facility.

REQUIREMENTS

-  **12' MINIMUM**
-  **12' RECOMMENDED**
-  **24' RECOMMENDED**
-  **208-230V, 1PH, 30A**
-  **90-120 PSI**

 **CONCRETE**
4" thick, reinforced, free from cracks/seams,
3500+ psi & cured 28+ days



MODEL # EV1020-XP9

 All Ingrounds are fully contained to eliminate any risk of environmental impact.

SPECIFICATIONS

MODEL NUMBER	EV1020XP9 / EV1020XP9-QC
Description	XP9 / XP9 & QuickCycle™
Lifting Capacity	9,000 lbs.
Arm Configuration	Drive-on Express Pad
Stroke	72"
Rise Height	74¾"
Overall Width	79½"
Drive Thru Clearance	NA
Arm Reach	NA
Platform Length x Width	58"/66½"/75" x 24"
Platform Width	2¾" Top of Deck or Bolt
Distance Between Platforms	31½"
Screw Pad Height	NA
Plunger Diameter	8½"
Standard Motor/Voltage*	2HP, 208v-230v, 60Hz, 1Ph / 3HP, 208v-230v, 60Hz, 1Ph
Rise Time	41s / 24s
Max. Load per Arm	4,500 lbs.
ALI® Certified	☒

SERVICE BAY LAYOUT

