

10K VERSYMMETRIC® 2-POST

CL10AV3

Challenger Lifts CL10AV3 model features our exclusive Versymmetric® technology to allow you to service the widest range of vehicles and maximize your bottom line. 3-stage front and 3-stage rear arms with our industry-first directSPOT™ design eliminate the need to shuffle a vehicle back and forth to swing the front arm clear of the tire to reach recommended lift points.

REQUIREMENTS

- 12' MINIMUM**
- 14' RECOMMENDED**
- 24' RECOMMENDED**
- 208-230V, 1PH, 20A**



SPECIFICATIONS

MODEL NUMBER	CL10AV3	CL10AV3-2	CL10AV3-3
Description	Standard	2' Extensions	3' Extensions
Lifting Capacity	10,000 lbs.		
Lift Configuration	Versymmetric®, 3-Stage Front & Rear		
Rise Height	74⅞"		
Height of Columns	11' 2" or 11' 8"	13' 2" or 13' 8"	14' 2" or 14' 8"
Max. Extended Cylinder Height	11' 11"		
Adjustable Width Overall	11' 6½"	12' ½"	12' 6½"
Drive Thru Clearance	(-12") 100"	(-6") 106"	(MAX) 112"
Floor to Overhead Switch	10' 8½" or 11' 2½"	12' 8½" or 12' 2½"	13' 8½" or 14' 2½"
Front Arm Reach	Min. 20" Max. 42"		
Rear Arm Reach	Min. 37⅝" Max. 60"		
Screw Pad Height	Min. 3⅞" Max. 6⅞"		
Inside Columns	(-12") 110"	(-6") 116"	(MAX) 122"
Low Lock Height	12" Net Rise		
Rise Time	Standard: 38s QuickCycle®: 24s (est.)		
Max. Load per Arm	2,500 lb.		
ALI® Certified	☒		

WIDTH CONFIGURATIONS

- Narrow:** Space Constraints or Express Pads configuration
- Universal:** Cars, SUVs, Trucks, Most Electric Vehicles
- Wide:** Optimal for Cars, EVs and Luxury vehicles

**The CL10A can also be set at the current 11' 10" width.*

