

15K HD 2-POST E15

Challenger's E15 is the perfect economic 2-Post lift for servicing trucks and other vehicles.

CONCRETE SPECS

4" thick, reinforced, free from cracks & seams, rated at 3500+ psi & cured minimum of 28 days

REQUIREMENTS

- 14' 7" MINIMUM**
- 14' RECOMMENDED**
- 24' RECOMMENDED**
- 208-230V, 1PH, 30A**

SPECIFICATIONS

| MODEL NUMBER | E15 |
|--------------------------|---|
| Lifting Capacity | 15,000lb |
| Rise Height | 6' 5 ³ / ₄ " |
| Overall Height | 14' 6" / 16' 6" |
| Overall Width | 12' 3 ¹ / ₆ " |
| Drive Thru Clearance | 9' 1 ¹ / ₈ " |
| Floor to Overhead Switch | 13' 10" / 15' 10" |
| Front Arm Reach | Min 36 ¹ / ₂ " Max 55" |
| Rear Arm Reach | Min 36 ¹ / ₂ " Max 55" |
| Screw Pad Height | Min 5 ¹ / ₄ " Max 6 ³ / ₄ " |
| Rise Time | 75s |
| Required Ceiling Height | 14' 7" / 16' 7" |
| Height Extension | No |
| ALI Certified | <input checked="" type="checkbox"/> |



SERVICE BAY LAYOUT

