

20K ADJUSTABLE HD CL20

Engineered to be wider, taller, and more robust to tackle the heaviest vehicles in your fleet, up to 20,000 lbs. Equipped with 2-Stage arms, this lift also features **adjustable column extensions, adjustable width and the ability to add optional 2' column extensions** for taller vehicles.



8' 8¼" **9' 2¼"** **9' 8¼"**

- 13' 6" MINIMUM**
- 16' RECOMMENDED**
- 28' RECOMMENDED**
- 208-230V, 1PH, 30A**
- 90-120 PSI**

MODEL NUMBER	CL20-0		CL20-2			
Description	20K Standard		20K Extended Height			
Lifting Capacity	20,000 lbs.					
Lift Configuration						
Arm Configuration	2-Stage Front & Rear					
Max. Load Per Arm	5,000 lbs.					
Rise Height	Min. 76⁹/₁₆" Max. 84⁹/₁₆" (with stack adapters)					
Overall Height Options	13' 6"	14'	14' 6"	15' 6"	16'	16' 6"
Floor to Overhead Switch	12' 11"	13' 5"	13' 11"	14' 11"	15' 5"	15' 11"
Arm Reach	Min. 38½" Max. 62"					
Screw Pad Height	Min. 6³/₁₆" Max. 7⁹/₁₆"					
Between Columns	Standard - 10' +6" - 10' 6" +12" - 11'					
Rise Time	62s					
Min. Ceiling Height Required	13' 8"	14' 2"	14' 8"	15' 8"	16' 2"	16' 8"
ALI Certified	<input checked="" type="checkbox"/>					

