





# OPEN-TOP 2-POST CLFP9

Challenger's 9,000 lb. capacity 2-post lift boasts standard 3-stage front and rear arms that offer maximum sweep, arm retraction, and reach.



## REQUIREMENTS

-  **10' 2" MINIMUM**
-  **14' RECOMMENDED**
-  **24' RECOMMENDED**
-  **208-230V, 1PH, 20A**

## CONCRETE SPECS

4" thick, reinforced, free from cracks & seams, rated at 3500+ psi & cured minimum of 28 days

## SERVICE BAY LAYOUT

## SPECIFICATIONS

MODEL NUMBER	VLE10
Rise Height	6' 5 <sup>7</sup> / <sub>8</sub> "
Overall Height	10' 7 <sup>7</sup> / <sub>8</sub> "
Overall Width	11' 5 <sup>1</sup> / <sub>2</sub> "
Drive Thru Clearance	8' 2 <sup>3</sup> / <sub>8</sub> "
Front Arm Reach	Min 24 <sup>1</sup> / <sub>2</sub> " Max 44 <sup>1</sup> / <sub>2</sub> "
Rear Arm Reach	Min 24 <sup>1</sup> / <sub>2</sub> " Max 44 <sup>1</sup> / <sub>2</sub> "
Screw Pad Height	Min 4" Max 6"
Rise Time	50s
Required Ceiling Height	10' 1 <sup>7</sup> / <sub>8</sub> "
ALI Certified	<input checked="" type="checkbox"/>

