

## 14K 4-POST 4P14

Challenger's 14,000 lb. closed-front drive-on 4-post lift features a low approach angle and wide runways for easy approach. It also has one of the highest rise in the industry and durable column construction.



### REQUIREMENTS

**↑ 78" + VEHICLE**

**← 14' RECOMMENDED**

**↓ 25' - 28' RECOMMENDED**

**⚡ 208-230V, 1PH, 20A**

**CONCRETE SPECS**  
4" thick, reinforced, free from cracks & seams,  
rated at 3500+ psi & cured minimum of 28 days

### SPECIFICATIONS

MODEL NUMBER	4P14EFX	4P14XFX
Rise Height	6' 6"	
Overall Length	20' 5 <sup>3</sup> / <sub>4</sub> "	22' 9 <sup>1</sup> / <sub>4</sub> "
Overall Width	10' 10 <sup>3</sup> / <sub>4</sub> "	
Inside Columns	9' 8"	
Between Columns	16' 4"	18' 7 <sup>1</sup> / <sub>2</sub> "
Height of Columns	7' 6 <sup>1</sup> / <sub>2</sub> "	
Width of Runways	20"	
Height of Runways	7 <sup>1</sup> / <sub>4</sub> "	
Width Between Runways	40" / 43"	
Rise Time	75s	
Min. Bay Size	14' x 25'	12' x 28'
ALI Certified	<input checked="" type="checkbox"/>	

### SERVICE BAY LAYOUT

