






30K HD 4-POST 4030 SERIES

A single-point air actuated lock release makes these lifts simple to use. Choose between general service or alignment deck models as well as three lengths to fit your shop's needs.

REQUIREMENTS

-  **72" + VEHICLE**
-  **28' RECOMMENDED**
-  **17' RECOMMENDED**
-  **208-230V, 1PH, 30A**
-  **90-120 PSI**

SPECIFICATIONS

MODEL NUMBER	4030SFX	4030EFX	4030XFX	4030SAX	4030EAX	4030XAX
Description	Short, Closed-Front, Flat Deck	Standard, Closed-Front, Flat Deck	Extended Length, Closed-Front, Flat Deck	Short, Closed-Front, Alignment Deck	Standard, Closed-Front, Alignment Deck	Extended Length, Closed-Front, Alignment Deck
Lifting Capacity	30,000 lbs.					
Overall Length (A)	308"	344"	380"	308"	344"	380"
Overall Width (B)	172.75"					
Inside Columns (C)	152"					
Between Columns (D)	246.125"	282.625"	318.625"	246.125"	282.625"	318.625"
Overall Height (E)	92.25"					
Height of Runways (F)	8.5"					
Width of Runways (G)	24"					
Width Between Runways (H)	46" - 52"					
Max Wheelbase (I)	244.5"	281"	317"	244.5"	281"	317"
Rise Height (J)	71.75"					
Max. 2-Wheel Alignment	-			219.5"	256"	292"
Standard Motor / Voltage	3HP, 208v - 230v					
Rise Time	126s					
Concrete Specifications	4" thick, reinforced, free from cracks/seams, rated at 3500+ psi and cured at least 28 days					
Required Bay Size W x L	17' x 28'	17' x 31'	17' x 34'	17' x 28'	17' x 31'	17' x 34'

