

OPEN-TOP 2-POST CLFP9

Challenger's 9,000 lb. capacity 2-post lift boasts standard 3-stage front and rear arms that offer maximum sweep, arm retraction, and reach.



REQUIREMENTS

	10' 2" MINIMUM
	14' RECOMMENDED
	24' RECOMMENDED
	208-230V, 1PH, 20A

CONCRETE SPECS

4" thick, reinforced, free from cracks & seams, rated at 3500+ psi & cured minimum of 28 days

SERVICE BAY LAYOUT

SPECIFICATIONS

MODEL NUMBER	CLFP9
Rise Height	6' 5 $\frac{5}{8}$ "
Overall Height	10' 7 $\frac{7}{8}$ "
Overall Width	11' 5 $\frac{1}{2}$ "
Drive Thru Clearance	8' 2 $\frac{3}{8}$ "
Front Arm Reach	Min 24 $\frac{1}{2}$ " Max 44 $\frac{1}{2}$ "
Rear Arm Reach	Min 24 $\frac{1}{2}$ " Max 44 $\frac{1}{2}$ "
Screw Pad Height	Min 4" Max 6"
Rise Time	50s
Required Ceiling Height	10' 1 $\frac{1}{8}$ "
ALI Certified	☒

